

ASSET AND VEHICLE LOCATORS

Starfinder Lite S

Global 4G LTE Vehicle Locator for Anti-theft and Fleet Management



Starfinder Lite S

Ideal for fleet management, vehicle protection, transport logistics and construction equipment protection





Key Features



4G LTE with GNSS



Time Interval & Distance Travelled Reports



Tow Alerts



Over Speeding Alerts



Geofence Violation Alerts



Driver Performance Reports



I/O Remote Control Interface



Missing Main Power Alerts

Ideal Applications



A Fleet of V



Valuable transportation



able Personal



Assets under



GNSS Satellites



Starfinder



How it Works

4G Cell



Interne



rnet locationnow.co

The ideal applications for Starfinder Lite S are Fleet management, Vehicle protection, Transport logistics and Construction equipment protection.

- Access a proprietary monitoring platform, and
- Return for Investment

Track individual or groups of devices in multiple locations all at once from our monitoring platform

LocationNow.com



Technical





| Specifications | | | |
|--|---|---|---|
| | Kamel S - NA | Kamel S - E | Starfinder Lite S |
| Attaching Mechanism | Magnet or Permanent Mount | Magnet or Permanent Mount | Bracket |
| Dimension | W: 7.50" x H: 3.87" x D: 2.43" | W: 7.50" x H: 3.87" x D: 2.43" | W: 2.32" x H: 1.02" x D: 3.74" |
| Weight | 2 lbs | 2 lbs | 0.20 lbs |
| Case Material | Hardened Poly Carbonate | Hardened Poly Carbonate | Aluminum |
| 4G LTE Compatibility | US, Canada, Mexico and LATAM | Europe, Middle East, Asia & Australia | Worldwide |
| SIM | Nano SIM | Nano SIM | Nano SIM |
| AGPS (AGNSS) | ✓ | ✓ | ✓ |
| GNSS and Cellular Signal Status | ✓ | ✓ | ✓ |
| Time interval or Distance Travelled Reports | ~ | ✓ | ✓ |
| Real-Time Location Report | ✓ | ✓ | ✓ |
| G-Sensor for Crash Alert | ✓ | ✓ | ✓ |
| Tow Alert | ✓ | ✓ | ✓ |
| Over Speeding Alert | ~ | ~ | ~ |
| Backup Battery | 18 A/h | 18 A/h | 900 mA/h |
| Programmable Geofences | 20 Geofences | 20 Geofences | 20 Geofences |
| Main Power Missing Alert | _ | _ | ~ |
| GPS NMEA Output | _ | _ | ~ |
| Data Logger | 22,000 Events | 22,000 Events | 22,000 Events |
| Data Port | _ | _ | USB C |
| External Antennas | _ | _ | GNSS and 4G |
| Input/Output | _ | _ | 3 Input and 3 Output |
| I/O Interface Cables | _ | _ | ✓ |
| Power Cables | _ | _ | ✓ |
| Supply Voltage | _ | _ | 9V - 36V DC |
| Low Battery Alert | ✓ | ✓ | _ |
| Battery Duration | Up to 1 Year depending on pings/day | Up to 1 Year depending on pings/day | _ |
| OTA Firmware Update | ✓ | ~ | ✓ |
| | | | |



Fast Charger AC-DC Included





